

IN THE CLAIMS:

1. (Original) A recording medium used for storing data, comprising:
a digital stream generated by multiplexing a video stream and a graphics stream,
wherein:

5 the graphic stream is a sequence of a plurality of packets which include a packet
containing control information; and

the control information indicates that graphic data contained in a preceding packet
in the sequence is to be displayed at a predetermined time in a state of being overlaid on the
video stream.

10 2. (Previously Presented) The recording medium of claim 1, wherein:
each of the plurality of packets belongs to any of a plurality of display sets which
are each used for reproducing a graphics display;

the graphics data and the control information belong to different display sets.

15 3. (Previously Presented) The recording medium of Claim 2, wherein the display
sets further comprise:

a Epoch Start DS having information necessary for displaying a next screen
composition and is provided at the start of memory management on a reproduction time axis;

an Acquisition Point DS having information necessary for displaying a next
screen composition; and

20 a Normal Case DS having difference information from a previous screen
composition;

wherein the Epoch Start DS is provided at the start of a memory management on a reproduction time axis and the Acquisition Point DS and the Normal Case DS are provided at a point other than the start of the memory management; and

the graphic data belongs either to the Epoch Start DS or the Acquisition Point DS,
5 and the control information belongs to the Normal Case DS.

4.-5. (Cancelled)

6. (Previously Presented) The recording medium of Claim 3, wherein:

the Epoch Start DS includes window information for defining an area of displaying the graphic data;

10 the window information specifies a position, a height, and a width of a window on a screen, the window being an area in which the graphics data is to be rendered when overlaying the graphics data on the video stream; and

the control information indicates that the graphics data is to be positioned within the window.

15 7. (Currently Amended) A reproduction apparatus for reproducing a digital stream generated by multiplexing a video stream and a graphics stream, comprising:

a video decoder operable to decode the video stream to generate a moving picture;
and

a graphic decoder operable to decode the graphics stream to generate graphics,
20 and overlay the graphics and the moving picture, wherein

upon reading control information in the graphics stream, the graphics decoder ~~displays~~ transfers graphics which has been generated by decoding graphics data that precedes the control information in the graphics stream to a plane memory, based on the control information.

8. (Previously Presented) The reproduction apparatus of Claim 7, wherein:

5 the graphics stream includes a plurality of display sets each of which is used for producing a graphics display; and

upon reading the display set to which the graphics data belongs, the graphics decoder decodes the graphics data to generate the graphics and stores the generated graphics to an object buffer.

10 9. (Currently Amended) The reproduction apparatus of Claim 8, ~~further comprising~~ a wherein the plane memory is memory for multiplexing overlaying the graphics and the video, ~~wherein the display sets further comprise~~ comprising:

a Epoch Start DS having information necessary for displaying a next screen composition and is provided at the start of memory management on a reproduction time axis;

15 an Acquisition Point DS having information necessary for displaying a next screen composition; and

a Normal Case DS having difference information from a previous screen composition;

20 wherein the Epoch Start DS is provided at the start of a memory management on a reproduction time axis and the Acquisition Point DS and the Normal Case DS are provided at a point other than the start of the memory management;

the graphic data belongs either to the Epoch Start DS or the Acquisition Point DS,
and the control information belongs to the Normal Case DS; and

the reproduction apparatus continuously manage the object buffer and the plane
memory from one Epoch Start DS and before the next immediate Epoch Start DS on the
5 reproduction time axis.

10.-11. (Cancelled)

12. (Previously Presented) The reproduction apparatus of Claim 9, wherein:

the Epoch Start DS includes window information for defining an area of
displaying the graphic data;

10 the window information specifies a position, a height, and a width of a window on
a screen, the window being an area in which the graphics data is to be rendered when overlaying
the graphics data on the video stream; and

the graphics decoder displays the graphics by clearing the window specified by
the window information and writing the graphics into the window.

15 13. (Currently Amended) A method of recording onto a recording medium,
comprising the steps of:

generating application data; and

recording the application data to the recording medium, wherein:

20 the application data includes a digital stream generated by multiplexing a video
stream and a graphics stream;

the graphics stream is a sequence of a plurality of packets which include a packet
containing control information; and

the control information indicates that graphics data contained in a preceding packet in the sequence is to be displayed at a predetermined time in a state of being overlaid on the video stream.

14. (Currently Amended) A computer-readable program used in a computer for
5 reproducing a digital stream generated by multiplexing a video stream and a graphics stream, comprising:

program code operable to cause the computer to decode the video stream to generate a moving picture; and

program code operable to cause the computer to decode the graphics stream to
10 generate graphics, and overlay the graphics and the moving picture, wherein

upon reading control information in the graphics stream, graphics which has been generated by decoding graphics data that precedes the control information in the graphics stream is ~~displayed~~ transferred to a plane memory based on the control information.

15. (Currently Amended) A method of reproducing a digital stream generated by
15 multiplexing a video stream and a graphics stream, comprising ~~the steps of:~~

decoding the video stream to generate a moving picture; ~~[[and]]~~

decoding the graphics stream to generate graphics, ~~and overlaying the graphics and the moving picture, wherein~~ and

upon reading control information in the graphics stream, ~~the step of decoding the graphics stream displays~~ transferring graphics which has been generated by decoding graphics
20 data that precedes the control information in the graphics stream to a plane memory, based on the control information.